

Benchmark test results: Copilot+ PCs from ASUS compared to MacBook laptops

In this report, we assessed the following devices:

- Copilot+ PCs running Windows 11 Pro
 - AMD processors:
 - ASUS ProArt P16 (H7606W) with AMD Ryzen AI 9 HX 370
 - ◆ ASUS Vivobook S 14 with AMD Ryzen AI 9 365
 - ASUS Zenbook S 16 (UM5606W) with AMD Ryzen AI 9 HX 370
 - Intel processor:
 - ◆ ASUS 7enbook S with 14 Intel® Core™ Ultra 7 256V
- Apple® MacBook® laptops running macOS® Sequoia
 - Apple MacBook Air® 13" with Apple M2
 - Apple MacBook Air 15" with Apple M2
 - Apple MacBook Air 13" with Apple M3
 - Apple MacBook Air 15" with Apple M3
 - Apple MacBook Pro® 14" with Apple M3

We used three benchmarks for performance testing:

- Cinebench 2024
- Geekbench 6 Pro v6.2.2
- Speedometer 2.1 on Microsoft Edge v128.0.2739.67)

We tested battery life with four different tests:

- Windows ADK battery test Web browsing, which Microsoft created and has used extensively (Copilot+ PCs only)
- Windows ADK battery test Local video playback, which Microsoft created and has used extensively (Copilot+ PCs only)
- Custom battery test Web browsing, which PT created and has used extensively
- Custom battery test Local video playback, which PT created and has used extensively

We ran each benchmark on each device three times; here, we report the average scores we saw across the three runs. For all results, higher is better. (The Time to shut down metric in Windows ADK battery life is a projection of how long the battery should last before the system shuts down.) For complete results and hardware/software disclosures, see the science behind the report.

Test results

Copilot+ PCs running Windows 11 Pro

Table 1: Results of our testing on the ASUS Copilot+ PCs with AMD processors. For all results, higher is better. For complete results, see the science behind the report.

	ASUS ProArt P16 (H7606W) AMD Ryzen Al 9 HX 370	ASUS Vivobook S 14 AMD Ryzen Al 9 365	ASUS Zenbook S 16 (UM5606W) AMD Ryzen AI 9 HX 370
Cinebench 2024			
Multi-core – Average	1,200.3	912.0	740.3
Single-core – Average	115.6	113.3	114.3
Geekbench 6 Pro v6.2.2			
Multi-core – Average	15,265.3	14,424.3	13,493.3
Single-core – Average	2,887.0	2,866.6	2,820.3
Speedometer 2.1 on Edge v128.0.2739.67			
Runs per minute – Average	534.3	514.0	459.3
Windows ADK battery test – Web browsing (Bat	tery Saver Dim OFF)		
Total duration (min) – Average	422.7	555.9	686.7
Projected time to shut down (min) – Average	444.3	579.6	714.6
Windows ADK battery test – Local video playba	ck (Battery Saver Dim OFF)		
Total duration (min) – Average	658.9	781.5	1,094.3
Projected time to shut down (min) – Average	684.6	813.3	1,140.6
Custom battery test – Web browsing			
Total duration (min) – Average	413.0	540.0	655.6
Custom battery test – Local video playback			
Total duration (min) – Average	684.1	826.6	1,142.3

Table 2: Results of our testing on the ASUS Zenbook S 14 with an Intel Core Ultra 7 256V processor. For all results, higher is better. For complete results, see the science behind the report.

	ASUS Zenbook S 14 Intel Core Ultra 7 256V
Cinebench 2024	
Multi-core – Average	492.3
Single-core – Average	116.0
Geekbench 6 Pro v6.2.2	
Multi-core – Average	10,664.6
Single-core – Average	2,558.6
Speedometer 2.1 on Edge v128.0.2739.67	
Runs per minute – Average	404.0
Windows ADK battery test – Web browsing (Batt	ery Saver Dim OFF)
Total duration (min) – Average	844.7
Projected time to shut down (min) – Average	880.3
Windows ADK battery test – Local video playbac	k (Battery Saver Dim OFF)
Total duration (min) – Average	1,335.4
Projected time to shut down (min) – Average	1,393.6
Custom battery test – Web browsing	
Total duration (min) – Average	833.5
Custom battery test – Local video playback	
Total duration (min) – Average	1,309.2

Apple MacBook laptops

Table 3: Results of our testing on the Apple devices we tested. For all results, higher is better. For complete results, see the science behind the report.

	Apple MacBook Pro 14" Apple M3	Apple MacBook Pro 14" Apple M3	Apple MacBook Air 15" Apple M2	Apple MacBook Air 15" Apple M2	Apple MacBook Air 13" Apple M2	Apple MacBook Air 13" Apple M3	Apple MacBook Air 13" Apple M3	Apple MacBook Air 15" Apple M3	Apple MacBook Air 15" Apple M3
Cinebench 2024									
Multi-core – Average	708.6	704.0	558.3	557.3	542.6	575.6	592.0	637.0	635.3
Single-core – Average	142.0	142.0	118.0	118.0	118.0	142.0	142.0	141.6	141.0
Geekbench 6 Pro	v6.2.2								
Multi-core – Average	12,044.3	12,049.0	12,044.3	12,049.0	10,150.6	12,038.0	12,004.6	12,044.0	12,029.3
Single-core – Average	3,125.0	3,133.0	2,623.6	2,622.0	2,613.0	3,039.3	3,037.0	3,047.0	3,061.3
Speedometer 2.1	on Edge v128.0.2739	9.67							
Runs per minute – Average	739.6	744.6	640.2	646.3	643.0	729.3	726.0	728.4	719.0
Custom battery te	est – Web browsing								
Total duration (min) – Average	745.2	709.5	671.4	715.3	656.9	703.9	710.2	699.2	688.9
Custom battery te	est – Local video playl	pack							
Total duration (min) – Average	1,091.5	1,043.8	803.0	838.7	805.4	901.8	904.0	841.3	820.3

Comparing the Copilot+ PCs to the Apple MacBook laptops

Table 4: For all benchmarks, the lowest average result, the highest average result, and the average of average results for the Copilot+ PCs we tested, the M2 processor-powered MacBook Air devices we tested, the M3 processor-powered MacBook Air devices we tested, and the M3 processor-powered MacBook Pro devices we tested. For all results, higher is better.

	Copilot+ PC (ASUS) devices we tested	M2 processor-powered MacBook Air systems we tested	M3 processor-powered MacBook Air systems we tested	M3 processor-powered MacBook Pro systems we tested
Cinebench 2024				
Multi-core – Lowest average across the group of devices	492.3	542.6	575.6	704.0
Multi-core – Highest average across the group of devices	1,200.3	558.3	637.0	708.6
Multi-core – Average of averages across the group of devices	836.2	552.7	610.0	706.3
Single-core – Lowest average across the group of devices	113.3	118.0	141.0	142.0
Single-core – Highest average across the group of devices	116.0	118.0	142.0	142.0
Single-core – Average of averages across the group of devices	114.8	118.0	141.6	142.0
Geekbench 6 Pro v6.2.2				
Multi-core – Lowest average across the group of devices	10,664.6	10,150.6	12,004.6	12,044.3
Multi-core – Highest average across the group of devices	15,265.3	12,049.0	12,044.0	12,049.0
Multi-core – Average of averages across the group of devices	13,461.9	11,414.6	12,029.0	12,046.6
Single-core – Lowest average across the group of devices	2,558.6	2,613.0	3,037.0	3,125.0
Single-core – Highest average across the group of devices	2,887.0	2623.6	3,061.3	3,133.0
Single-core – Average of averages across the group of devices	2,783.2	2,619.5	3,046.1	3,129.0
Speedometer 2.1 on Edge v128.0.2739.67				
Runs per minute – Lowest average across the group of devices	404.0	640.2	719.0	739.6
Runs per minute – Highest average across the group of devices	534.3	646.3	729.3	744.6
Runs per minute – Average of averages across the group of devices	477.9	643.2	725.6	742.1
Windows ADK battery test – Web browsing (Battery Saver Dim OFF)				
Total duration (min) – Lowest average across the group of devices	422.7			
Total duration (min) – Highest average across the group of devices	844.7			
Total duration (min) – Average of averages across the group of devices	627.5			
Projected time to shut down (min) – Lowest average across the group of devices	444.3			
Projected time to shut down (min) – Highest average across the group of devices	880.3			
Projected time to shut down (min) – Average of averages across the group of devices	654.7			

	Copilot+ PC (ASUS) devices we tested	M2 processor-powered MacBook Air systems we tested	M3 processor-powered MacBook Air systems we tested	M3 processor-powered MacBook Pro systems we tested
Windows ADK battery test – Local video playback (Battery Saver Dim OFF)				
Total duration (min) – Lowest average across the group of devices	658.9			
Total duration (min) – Highest average across the group of devices	1,335.4			
Total duration (min) – Average of averages across the group of devices	967.5			
Projected time to shut down (min) – Lowest average across the group of devices	684.6			
Projected time to shut down (min) – Highest average across the group of devices	1,293.6			
Projected time to shut down (min) – Average of averages across the group of devices	1,008.0			
Custom battery test – Web browsing	'			
Total duration (min) – Lowest average across the group of devices	413.0	656.9	688.9	709.5
Total duration (min) – Highest average across the group of devices	833.5	715.3	710.2	745.2
Total duration (min) – Average of averages across the group of devices	610.5	681.2	700.5	727.4
Custom battery test – Local video playback	,	,		
Total duration (min) – Lowest average across the group of devices	684.1	803.0	820.3	1,043.8
Total duration (min) – Highest average across the group of devices	1,309.2	838.7	904.0	1,091.5
Total duration (min) – Average of averages across the group of devices	990.6	815.7	866.8	1,067.6

The science behind the report

In this section, we list our complete results and describe the solutions on which we tested and our test methodologies.

We concluded our hands-on testing on October 29, 2024. During testing, we determined the appropriate hardware and software configurations and applied updates as they became available. The results in this report reflect configurations that we finalized on October 11, 2024 or earlier. Unavoidably, these configurations may not represent the latest versions available when this report appears.

Our results

To learn more about how we have calculated the wins in this report, go to http://facts.pt/calculating-and-highlighting-wins. Unless we state otherwise, we have followed the rules and principles we outline in that document

Copilot+ PCs running Windows 11 Pro

Table 5: Results of our testing on the ASUS Copilot+ PCs with AMD processors. For all results, higher is better.

	ASUS ProArt P16 (H7606W) AMD Ryzen AI 9 HX 370	ASUS Vivobook S 14 AMD Ryzen AI 9 365	ASUS Zenbook S 16 (UM5606W) AMD Ryzen AI 9 HX 370
Cinebench 2024			
Multi-core – Run 1	1,203	925	739
Multi-core – Run 2	1,190	881	740
Multi-core – Run 3	1,208	930	742
Single-core – Run 1	115	112	114
Single-core – Run 2	116	114	114
Single-core – Run 3	116	114	115
Multi-core – Average	1,200.3	912	740.3
Single-core – Average	115.6	113.3	114.3

	ASUS ProArt P16 (H7606W) AMD Ryzen Al 9 HX 370	ASUS Vivobook S 14 AMD Ryzen AI 9 365	ASUS Zenbook S 16 (UM5606W) AMD Ryzen AI 9 HX 370
Geekbench 6 Pro v6.2.2			
Multi-core – Run 1	15,362	14,471	13,420
Multi-core – Run 2	15,180	14,404	13,586
Multi-core – Run 3	15,254	14,398	13,474
Single-core – Run 1	2,884	2,871	2,811
Single-core – Run 2	2,892	2,860	2,831
Single-core – Run 3	2,885	2,869	2,819
Multi-core – Average	15,265.3	14,424.3	13,493.3
Single-core – Average	2,887.0	2,866.6	2,820.3
Speedometer 2.1 on Edge v128.0.2739.67			
Runs per minute – Run 1	536	512	470
Runs per minute – Run 2	539	512	455
Runs per minute – Run 3	528	518	453
Runs per minute – Average	534.3	514.0	459.3
Windows ADK battery test – Web browsing (Bat	ttery Saver Dim OFF)		
Total duration (min) - Run 1	425.5	534.1	667.7
Projected time to shut down (min) - Run 1	460.0	561.0	695.0
Total duration (min) - Run 2	422.0	567.4	675.6
Projected time to shut down (min) - Run 2	437.0	590.0	703.0
Total duration (min) - Run 3	420.5	566.3	716.7
Projected time to shut down (min) - Run 3	436.0	588.0	746.0
Total duration (min) – Average	422.7	555.9	686.7
Projected time to shut down (min) – Average	444.3	579.6	714.6

	ASUS ProArt P16 (H7606W) AMD Ryzen Al 9 HX 370	ASUS Vivobook S 14 AMD Ryzen AI 9 365	ASUS Zenbook S 16 (UM5606W) AMD Ryzen AI 9 HX 370
Windows ADK battery test – Local video playbac	ck (Battery Saver Dim OFF)		
Total duration (min) - Run 1	656.6	773.4	1,100.1
Projected time to shut down (min) - Run 1	682.0	805.0	1,147.0
Total duration (min) - Run 2	667.8	792.8	1,092.8
Projected time to shut down (min) - Run 2	694.0	825.0	1,139.0
Total duration (min) - Run 3	652.3	778.3	1,090.1
Projected time to shut down (min) - Run 3	678.0	810.0	1,136.0
Total duration (min) – Average	658.9	781.5	1,094.3
Projected time to shut down (min) – Average	684.6	813.3	1,140.6
Custom battery test – Web browsing			
Total duration (min) - Run 1	409.3	540.7	626.0
Total duration (min) - Run 2	424.3	523.7	671.9
Total duration (min) - Run 3	405.3	555.7	669.0
Total duration (min) – Average	413.0	540.0	655.6
Custom battery test – Local video playback			
Total duration (min) - Run 1	687.1	816.9	1,130.8
Total duration (min) - Run 2	682.6	843.0	1,141.6
Total duration (min) - Run 3	682.6	819.9	1,154.7
Total duration (min) – Average	684.1	826.6	1,142.4

Table 6: Results of our testing on the ASUS Zenbook S 14 with an Intel Core Ultra 7 256V processor. For all results, higher is better.

	ASUS Zenbook S 14 Intel Core Ultra 7 256V
Cinebench 2024	
Multi-core – Run 1	478
Multi-core – Run 2	497
Multi-core – Run 3	502
Single-core – Run 1	112
Single-core – Run 2	118
Single-core – Run 3	118
Multi-core – Average	492.3
Single-core – Average	116.0
Geekbench 6 Pro v6.2.2	
Multi-core – Run 1	10,681
Multi-core – Run 2	10,608
Multi-core – Run 3	10,705
Single-core – Run 1	2,569
Single-core – Run 2	2,556
Single-core – Run 3	2,551
Multi-core – Average	10,664.6
Single-core – Average	2,558.6
Speedometer 2.1 on Edge v128.0.2739.67	
Runs per minute – Run 1	395
Runs per minute – Run 2	415
Runs per minute – Run 3	402
Runs per minute – Average	404.0

	ASUS Zenbook S 14 Intel Core Ultra 7 256V
Windows ADK battery test – Web browsing (Batt	tery Saver Dim OFF)
Total duration (min) - Run 1	830.0
Projected time to shut down (min) - Run 1	865.0
Total duration (min) - Run 2	837.6
Projected time to shut down (min) - Run 2	873.0
Total duration (min) - Run 3	866.4
Projected time to shut down (min) - Run 3	903.0
Total duration (min) – Average	844.7
Projected time to shut down (min) – Average	880.3
Windows ADK battery test – Local video playbac	ck (Battery Saver Dim OFF)
Total duration (min) - Run 1	1,346.5
Projected time to shut down (min) - Run 1	1,406.0
Total duration (min) - Run 2	1,330.3
Projected time to shut down (min) - Run 2	1,388.0
Total duration (min) - Run 3	1,329.3
Projected time to shut down (min) - Run 3	1,387.0
Total duration (min) – Average	1,335.4
Projected time to shut down (min) – Average	1,393.6
Custom battery test – Web browsing	
Total duration (min) - Run 1	850.5
Total duration (min) - Run 2	798.4
Total duration (min) - Run 3	851.5
Total duration (min) – Average	833.5
Custom battery test – Local video playback	
Total duration (min) - Run 1	1,245.1
Total duration (min) - Run 2	1,320.2
Total duration (min) - Run 3	1,362.4
Total duration (min) – Average	1,309.2

Apple MacBook laptops

Table 7: Results of our testing on the Apple devices we tested. For all results, higher is better.

	Apple MacBook Pro 14" Apple M3	Apple MacBook Pro 14" Apple M3	Apple MacBook Air 15" Apple M2	Apple MacBook Air 15" Apple M2	Apple MacBook Air 13" Apple M2	Apple MacBook Air 13" Apple M3	Apple MacBook Air 13" Apple M3	Apple MacBook Air 15" Apple M3	Apple MacBook Air 15" Apple M3
Cinebench 2024									
Multi-core – Run 1	704.0	700.0	559.0	558.0	545.0	581.0	600.0	637.0	635.0
Multi-core – Run 2	709.0	702.0	555.0	554.0	546.0	583.0	599.0	641.0	636.0
Multi-core – Run 3	713.0	710.0	561.0	560.0	537.0	563.0	577.0	633.0	635.0
Single-core – Run 1	142.0	142.0	118.0	118.0	118.0	142.0	142.0	141.0	141.0
Single-core – Run 2	142.0	142.0	118.0	118.0	118.0	142.0	142.0	142.0	141.0
Single-core – Run 3	142.0	142.0	118.0	118.0	118.0	142.0	142.0	142.0	141.0
Multi-core – Average	708.6	704.0	558.3	557.3	542.6	575.6	592.0	637.0	635.3
Single-core – Average	142.0	142.0	118.0	118.0	118.0	142.0	142.0	141.6	141.0
Geekbench 6 Pro	v6.2.2								
Multi-core – Run 1	12,078.0	12,054.0	10,135.0	10,170.0	10,152.0	12,006.0	12,029.0	11,969.0	12,054.0
Multi-core – Run 2	12,076.0	12,027.0	10,131.0	10,134.0	10,166.0	12,029.0	11,948.0	12,079.0	12,017.0
Multi-core – Run 3	11,979.0	12,066.0	10,100.0	10,141.0	10,134.0	12,079.0	12,037.0	12,084.0	12,017.0
Single-core – Run 1	3,122.0	3,135.0	2,626.0	2,624.0	2,610.0	3,033.0	3,028.0	3,045.0	3,049.0
Single-core – Run 2	3,134.0	3,137.0	2,623.0	2,622.0	2,610.0	3,043.0	3,043.0	3,046.0	3,065.0
Single-core – Run 3	3,119.0	3,127.0	2,622.0	2,620.0	2,619.0	3,042.0	3,040.0	3,050.0	3,070.0
Multi-core – Average	12,044.3	12,049.0	12,044.3	12,049.0	10,150.6	12,038.0	12,004.6	12,044.0	12,029.3
Single-core – Average	3,125.0	3,133.0	2,623.6	2,622.0	2,613.0	3,039.3	3,037.0	3,047.0	3,061.3

	Apple MacBook Pro 14" Apple M3	Apple MacBook Pro 14" Apple M3	Apple MacBook Air 15" Apple M2	Apple MacBook Air 15" Apple M2	Apple MacBook Air 13" Apple M2	Apple MacBook Air 13" Apple M3	Apple MacBook Air 13" Apple M3	Apple MacBook Air 15" Apple M3	Apple MacBook Air 15" Apple M3
Speedometer 2.1	on Edge v128.0.2739	9.67							
Runs per minute – Run 1	737.0	744.0	643.0	645.0	643.0	726.0	721.0	728.3.0	722.0
Runs per minute – Run 2	744.0	745.0	640.0	648.0	647.0	732.0	731.0	728.0	716.0
Runs per minute – Run 3	738.0	745.0	637.8	646.0	639.0	730.0	726.0	729.0	719.0
Runs per minute – Average	739.6	744.6	640.2	646.3	643.0	729.3	726.0	728.4	719.0
Custom battery te	st – Web browsing								
Total duration (min) - Run 1	747.6	709.6	672.2	719.6	663.5	697.6	705.6	706.6	696.6
Total duration (min) - Run 2	752.5	717.5	670.6	709.6	647.5	709.5	714.5	687.5	674.5
Total duration (min) - Run 3	735.6	701.5	671.6	716.6	659.5	704.5	710.5	703.5	695.5
Total duration (min) – Average	745.2	709.5	671.4	715.3	656.9	703.9	710.2	699.2	688.9
Custom battery te	st – Local video playk	pack							
Total duration (min) - Run 1	1,073.8	1,042.8	807.9	844.7	800.6	918.7	913.7	851.7	829.7
Total duration (min) - Run 2	1,121.8	1,059.7	801.6	838.7	812.7	903.9	899.6	848.6	805.6
Total duration (min) - Run 3	1,078.8	1,028.8	799.7	832.7	803.0	882.7	898.7	823.6	825.6
Total duration (min) – Average	1,091.5	1,043.8	803.0	838.7	805.4	901.8	904.0	841.3	820.3

System configuration information

Table 8: Detailed information on the systems we tested.

System configuration information	ASUS ProArt P16 (H7606W)	ASUS Zenbook S 16 (UM5606W)	ASUS ProArt P16 (H7606W)	ASUS Zenbook S 16 (UM5606W)			
Processor							
Vendor	AMD	AMD	AMD	AMD			
Model number	Ryzen Al 9 HX 370	Ryzen Al 9 HX 370	Ryzen Al 9 HX 370	Ryzen AI 9 HX 370			
Core frequency (GHz)	2-5.1	2-5.1	2-5.1	2-5.1			
Number of cores	12	12	12	12			
Memory							
Amount (GB)	64	32	64	32			
Туре	LPDDR5X	LPDDR5X	LPDDR5X	LPDDR5X			
Graphics							
Vendor	NVIDIA®	AMD	NVIDIA	AMD			
Model number	RTX 4070 Laptop GPU	Radeon 890M Graphics	RTX 4070 Laptop GPU	Radeon 890M Graphics			
Storage							
Amount	2 x 2TB	1 TB	2 x 2TB	1 TB			
Туре	SSD	SSD	SSD	SSD			
Connectivity/expansion							
Wireless internet	eless internet MediaTek Wi-Fi 7 MT7925 MediaTek Wi-Fi		MediaTek Wi-Fi 7 MT7925				
Battery							
Rated capacity (Wh)	90	78	90	78			
Display							
Size (inches)	16	16	16	16			
Resolution	3,840 x 2,400	2,880 x 1,800	3,840 x 2,400	2,880 x 1,800			
Operating system							
Vendor	Microsoft	Microsoft	Microsoft	Microsoft			
Name	Windows 11 Pro	Windows 11 Pro	Windows 11 Pro	Windows 11 Pro			
Version	24H2 Build 26100.1591	24H2 Build 26100.1742	24H2 Build 26100.1591	24H2 Build 26100.1742			

System configuration information	ASUS ProArt P16 (H7606W)	ASUS Zenbook S 16 (UM5606W)	ASUS ProArt P16 (H7606W)	ASUS Zenbook S 16 (UM5606W)					
BIOS									
BIOS name and version	American Megatrends International, LLC. H7606WI.308			American Megatrends International, LLC. UM5606WA.309					
Dimensions									
Height (inches)	0.59- 0.68		0.59- 0.68	0.47- 0.51					
Width (inches)	13.97	13.92	13.97	13.92					
Depth (inches)	9.72 9.57 9.72		9.57						
Weight (lbs.) 4.02		3.31	4.02	3.31					

Table 9: Detailed information on the Apple systems we tested.

System configuration information	Apple MacBook Pro 14" Apple M3	Apple MacBook Pro 14" Apple M3	Apple MacBook Air 15" Apple M2	Apple MacBook Air 15" Apple M2	Apple MacBook Air 13" Apple M2	Apple MacBook Air 13" Apple M3	Apple MacBook Air 13" Apple M3	Apple MacBook Air 15" Apple M3	Apple MacBook Air 15" Apple M3
Processor									
Vendor	Apple								
Model number	M3	M3	M2	M2	M2	M3	M3	M3	M3
Core frequency (GHz)	4.05	4.05	3.49	3.49	3.49	4.05	4.05	4.05	4.05
Number of cores	8	8	8	8	8	8	8	8	8
Memory									
Amount (GB)	8	8	8	8	8	8	8	8	8
Туре	Unified								
Graphics			1					-	
Vendor	Apple								
Model number	M3 10-core GPU	M3 10-core GPU	M2 10-core GPU	M2 10-core GPU	M2 8-core GPU	M3 8-core GPU	M3 8-core GPU	M3 10-core GPU	M3 10-core GPU
Storage	1	1		1					
Amount (GB)	512	512	256	256	256	256	256	256	256
Туре	SSD								

System configuration information	Apple MacBook Pro 14" Apple M3	Apple MacBook Pro 14" Apple M3	Apple MacBook Air 15" Apple M2	Apple MacBook Air 15" Apple M2	Apple MacBook Air 13" Apple M2	Apple MacBook Air 13" Apple M3	Apple MacBook Air 13" Apple M3	Apple MacBook Air 15" Apple M3	Apple MacBook Air 15" Apple M3
Connectivity/expa	nsion								
Wireless internet	Wi-Fi 6E	Wi-Fi 6E	Wi-Fi 6	Wi-Fi 6	Wi-Fi 6	Wi-Fi 6E	Wi-Fi 6E	Wi-Fi 6E	Wi-Fi 6E
Battery									
Rated capacity (Wh)	70	70	66.5	66.5	52.6	52.6	52.6	66.5	66.5
Display									
Size (inches)	14.2	14.2	15.3	15.3	13.6	13.6	13.6	15.3	15.3
Resolution	3,024 x 1,964	3,024 x 1,964	2,880 x 1,864	2,880 x 1,864	2,560 x 1,664	2,560 x 1,664	2,560 x 1,664	2,880 x 1,864	2,880 x 1,864
Operating system	1		I			•			
Vendor	Apple								
Name	macOS Sequoia								
Version	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
BIOS									
BIOS name and version	N/A								
Dimensions									
Height (inches)	0.61	0.61	0.45	0.45	0.44	0.44	0.44	0.45	0.45
Width (inches)	12.31	12.31	13.40	13.40	11.97	11.97	11.97	13.40	13.40
Depth (inches)	8.71	8.71	9.35	9.35	8.46	8.46	8.46	9.35	9.35
Weight (lbs.)	3.4	3.4	3.3	3.3	2.7	2.7	2.7	3.3	3.3

How we tested

Setting up the systems (Windows)

Setting up and updating the OEM image

- 1. Boot the system.
- 2. Follow the on-screen instructions to complete installation, using the default selections when appropriate.
- 3. Set the Windows (plugged in) Power Mode to Best Performance.
- 4. Set Screen and Sleep options to Never:
 - Right-click the desktop, and select Display settings.
 - Select System from the left-hand column.
 - Click Power & Battery.
 - For all power options listed under Screen and Sleep, select Never.
- Disable User Account Control notifications.
 - Select Windows Start, type UAC and press Enter.
 - Move the slider control to Never notify, and click OK.
- 6. Run Windows Update, and install all updates available.
- 7. Verify the date and time are correct, and synchronize the system clock with the time server.
- 8. Pause Automatic Windows Updates.
 - Click the Windows Start button.
 - Type Windows Update settings and press Enter.
 - From the Pause updates drop-down menu, select Pause for 5 weeks.

Measuring performance (Windows)

Cinebench 2024 benchmark

Setting up the test

 Download and install Cinebench from https://www.maxon.net/en/downloads/cinebench-2024-downloads.

Running the benchmark

- 1. Launch Cinebench.
- 2. Select File→Advanced benchmark.
- 3. Set the Minimum Test Duration to Off.
- 4. Select CPU (Multi Core), CPU (Single Core), or GPU, and click Start
- 5. Record the result.
- 6. Wait 15 minutes before re-running.
- 7. Repeat steps 1 through 6 twice more, and report the averages of the results.

Geekbench 6 Pro

Setting up the test

1. Purchase a Pro license, and download and install Geekbench 6 Pro from https://www.geekbench.com/download/.

Running the test

- 1. Launch Geekbench.
- Click Run CPU Benchmark.
- 3. Record the result.
- 4. Wait 5 minutes before re-running.
- 5. Repeat steps 1 through 4 twice more, and report the averages of the results.

3DMark

Setting up the test

- 1. Download 3DMark from http://www.futuremark.com/benchmarks/3dmark/all.
- 2. To install 3DMark with the default options, double-click the 3DMark installer.exe file.
- 3. To launch 3DMark, double-click the 3DMark desktop icon.
- 4. Enter the registration code, and click Register.
- 5. Exit 3DMark.

Running the test

- Launch the 3Dmark benchmark.
- 2. At the 3DMark Home screen, underneath the Wild Life Extreme Benchmark, click Run.
- 3. When the benchmark run completes, record the results.
- 4. Perform steps 2 through 3 twice more, and report the averages of the results.

Speedometer 2.1

Running the test

- 1. In a browser, navigate to https://browserbench.org/Speedometer2.1/.
- 2. Click Start Test.
- 3. When the benchmark run completes, record the results.
- 4. Perform steps 2 through 3 twice more, and report the averages of the results.

Measuring battery life (Windows)

Windows ADK: Local video playback battery rundown

Setting up the test

- 1. Verify that the displays will remain constant during the test:
 - Right-click the desktop and select Display settings.
 - Uncheck the box next to Change brightness automatically when lighting changes, if available.
 - Uncheck the box next to Change brightness based on content, if available.
 - Select System from the left-hand column.
 - · Click Power & Battery.
 - For all power options listed under Screen and Sleep, select Never.
 - Set Turn battery saver on automatically at 20%.
 - Uncheck the box next to Lower screen brightness when user battery saver.
- 2. Create a folder on the root of C:\ named data
- 3. Create a folder on the root of C:\ named adk
- Place adk test files into the C:\data\ folder.
- 5. Move the contents of the EE_LFSVP_ToS folder into the C:\adk\ folder.
- 6. Using a nit meter, adjust the screen brightness to as close to 150 nits as possible.
- 7. Open PowerShell as administrator and run Set-ExecutionPolicy bypass
- 8. Type A to choose yes to all, and press enter.
- 9. Run Get-ChildItem -Path 'C:\adk' -Recurse | Unblock-File
- 10. Navigate to C:\data\prep\.
- 1. Enter runme.bat to run the system prep command.

Running the test

- 1. After the prep command completes, wait 2 minutes before proceeding.
- 2. Open an elevated command prompt.
- 3. Navigate to C:\adk\
- 4. With the system plugged in and charged to 100%, enter runjob.cmd to run the local video playback battery rundown test.
- 5. Click Run job on this computer.
- 6. Click Start.
- 7. At the Assessment is Beginning screen, click next.
- 8. When prompted to unplug the system, do so.
- 9. When the test completes, record the results.
- 10. Plug the system in and charge back to 100%.
- 11. Repeat steps 2 through 10 twice more, and report the averages of the results.

Windows ADK: Web Browsing battery rundown

Setting up the test

- 1. Verify that the displays will remain constant during the test:
 - Right-click the desktop, and select Display settings.
 - Uncheck the box next to Change brightness automatically when lighting changes, if available.
 - Uncheck the box next to Change brightness based on content, if available.
 - Select System from the left column.
 - Click Power & Battery.
 - For all power options listed under Screen and Sleep, select Never.
 - Set Turn battery saver on automatically at 20%.
 - Uncheck the box next to Lower screen brightness when user battery saver.
- 2. Using a nit meter, adjust the screen brightness to as close to 150 nits as possible.
- Open Edge, and navigate to edge://settings/help to identify the version number for the Edge browser.
- 4. Apply any Edge updates that are available.
- 5. Open Device Manager, and make sure there are no yellow bangs or unknown devices.
- 6. Open the Microsoft Store, and update all applications.
- 7. Open PowerShell as administrator, and run Set-ExecutionPolicy bypass
- 8. Type A to choose yes to all, and press Enter.
- 9. Run winget upgrade -all -include-unknown
- Open the system settings, and make sure the date and time are synchronized on the system under test.
- 11. Disable any keyboard backlights.
- 12. Make sure the Microsoft Edge language is set to English at edge://settings/languages
- 13. In the Edge settings, remove any profiles that have been added.
- 14. Open an elevated command prompt.
- 15. Navigate to C:\data\prep\
- 16. Enter runme.bat to run the system prep command.

Running the test

- 1. After the prep command completes, wait 2 minutes before proceeding.
- 2. Create a folder on the root of C:\ named data.
- Place adk test files into the C:\data\ folder.
- 4. Navigate to https://developer.microsoft.com/en-us/microsoft-edge/tools/webdriver/
- Download the appropriate x64 or ARM64 version of the webdriver that matches the current Edge version number.
- 6. Extract msedgedriver.exe to C:\data\test\bin\
- 7. Open the parameters.abl.credentials.json file located in C:\data\ asmt\Assessment2\scenarios in notepad and enter the credentials for the outlook.com account used.
- 8. Open an elevated command prompt.
- 9. Run Get-ChildItem -Path 'C:\data' -Recurse | Unblock-File
- 10. Navigate to C:\data\asmt\
- 11. Run RunJobABLTraining.cmd

- 12. Click Start.
- 13. At the Assessment Beginning screen, click Next.
- 14. Unplug the system when prompted.
- 15. When the training command is complete, plug the system back in, and make sure it charges to 100%.
- 16. Open an elevated command prompt.
- 17. Navigate to C:\data\asmt\
- 18. Run RunJobABLTrained.cmd
- 19. When the test is complete, record the results and copy the results folder to Documents.
- 20. Plug the system in, and charge it back to 100%.
- 21. Open Explorer, and delete the entire C:\data folder.
- 22. Repeat steps 1 through 21 twice more, and report the averages of the results.

PT custom test: Local video playback battery rundown

Setting up the test

- 1. Turn on the systems.
- 2. Copy the test video file and battery life logger to each system.
- 3. In Explorer, right-click the script, and click Properties.
- 4. Check Unblock file, and click OK.
- 5. Verify that the displays will remain on during the test:
 - Right-click the desktop, and select Display settings.
 - Uncheck the box next to Change brightness automatically when lighting changes, if available.
 - Uncheck the box next to Change brightness based on content, if available.
 - Select System from the left column.
 - Click Power & Battery.
 - For all power options listed under Screen and Sleep, select Never.
 - Set Turn energy saver on automatically at 20%.
 - Check the box next to Lower screen brightness when using energy saver.
- 6. Set the system volume to 60 dbA with a decibel meter.
- 7. To bring up a white screen, open a web browser and type about:blank into the address bar.
- 8. Unplug the system.
- 9. Using a nit meter, adjust the screen brightness to as close to 150 nits as possible.
- 10. Plug in the system.
- 11. Open PowerShell as administrator and run Set-ExecutionPolicy Unrestricted
- 12. Type A to choose yes to all, and press enter.
- 13. Open Control Panel, and click Hardware and Sound.
- 14. Click Power Options, and click Change plan settings on the currently selected power plan.
- 15. Click Change advanced power settings.
- 16. Set the Low battery notification on Battery to Off.
- 17. Open Microsoft Store, click the profile button at the top, and click Settings.
- 18. Turn off App updates.

Running the test

- . Verify that the system's battery is fully charged.
- Open an elevated PowerShell and type start-process "C:\Program Files\Windows Defender\MpCmdRun.exe" ("BuildSFC -Timeout 7200000") -Wait.
- After the command completes, type start "rundll32.exe" ("advapi32.dll, ProcessIdleTasks") -Wait.
 Do not interact with the system until the command completes.
- 4. After the command completes, reboot the system.
- 5. Wait 5 minutes before proceeding.
- 6. Launch the test video file in full screen mode with Repeat enabled.
- Open an elevated PowerShellm and navigate to the directory containing the battery life logger script.
- 3. Type .\<battery script name>.ps1 and press Enter to run the script.
- 9. Unplug the system when prompted and switch back to the full screen video.
- 10. When the test is complete, plug in the system and start it.
- 11. In Explorer, navigate to C:\ptbat\.
- 12. Open the folder corresponding with the date and time of the test and record the results from batresults_minutes.txt.
- 13. Repeat steps 1 through 12 twice more, and report the averages of the results.

PT custom test: Web browsing battery rundown

Setting up the test

- 1. Turn on the systems.
- 2. Copy the battery life logger and website iterator to each system.
- 3. In Explorer, right-click each script, and click Properties.
- 4. Check Unblock file, and click OK.
- 5. Verify that the displays will remain constant during the test:
 - Right-click the desktop, and select Display settings.
 - Uncheck the box next to Change brightness automatically when lighting changes, if available.
 - Uncheck the box next to Change brightness based on content, if available.
 - Select System from the left column.
 - Click Power & Battery.
 - For all power options listed under Screen and Sleep, select Never.
 - Set Turn energy saver on automatically at 20%.
 - Check the box next to Lower screen brightness when using energy saver.
- 6. Set the system volume to 60 dbA with a decibel meter.
- 7. To bring up a white screen, open a web browser and type about:blank into the address bar.
- Unplug the system.
- 9. Using a nit meter, adjust the screen brightness to as close to 150 nits as possible.
- 0. Plug in the system.
- 11. Open PowerShell as administrator and run Set-ExecutionPolicy Unrestricted
- 12. Type A to choose yes to all and press enter.
- 13. Open Control Panel, and click Hardware and Sound.

- 14. Click Power Options, and click Change plan settings on the currently selected power plan.
- 15. Click Change advanced power settings.
- 16. Set the Low battery notification on Battery to Off.
- 17. Click the Windows start icon, and in the search field, type regedit. To open the Registry Editor, press Enter.
- 18. Navigate to HKEY_LOCAL_MACHINE→SOFTWARE→Policies→Microsoft→Edge.
- 19. If necessary, create the Edge folder by right-clicking in the right-hand pane, clicking New Key, and typing Edge.
- 20. Right-click in the right pane, click New DWORD (32-bit) Value, type HideRestoreDialogEnabled, and press enter.
- 21. Double-click HideRestoreDialogEnabled, and in the value data field, type 1. Click OK.
- 22. Open Microsoft Store, click the profile button at the top, and click Settings.
- 23. Turn off App updates.

Running the test

- 1. Verify that the system's battery is fully charged.
- Open an elevated PowerShell and type start-process "C:\Program Files\Windows
 Defender\MpCmdRun.exe" ("BuildSFC -Timeout 7200000") -Wait.
- 3. After the command completes, type start "rundll32.exe" ("advapi32.dll,ProcessIdleTasks") -Wait. Do not interact with the system until the command completes.
- 4. After the command completes, reboot the system.
- 5. Wait 5 minutes before proceeding.
- Open an elevated PowerShell and navigate to the directory containing the battery life logger script.
- 7. Type .\<battery script name>.ps1
- 8. Open a second elevated PowerShell and navigate to the directory containing the website iterator script.
- 9. Type .\<website script name>.ps1 -t
- 10. Click Enter in each PowerShell window to run both scripts.
- 11. Unplug the system when prompted.
- 12. When the test is complete, plug in the system and start it.
- 13. In Explorer, navigate to C:\ptbat\.
- 14. Open the folder corresponding with the date and time of the test and record the results from batresults_minutes.txt.
- 15. Repeat steps 1 through 14 twice more, and report the averages of the results.

Setting up the system (macOS)

Setting up and updating the OEM image

- Boot the system.
- 2. Follow the on-screen instructions to complete installation, using the default selections when appropriate.
- 3. Set Screen and Sleep options to Never.
 - Select System Settings.
 - Select Lock Screen.
 - Change the following options to Never:
 - Start Screen Saver when inactive.
 - Turn display off on battery when inactive.
 - Turn display off on power adapter when inactive.
 - Require password after screen saver begins or display is turned off.
 - Return to System Settings and select Battery.
 - Set On power adapter setting to High Power (Note: this is not an option available on all Macs).
 - Click Options.
 - Disable the Slightly dim the display on battery option.
- 4. Disable automatically adjust brightness.
 - Select System Settings.
 - Select Display.
 - Disable Automatically adjust brightness.
- 5. Run Software Update, and install all updates available.
- 6. Verify the date and time are correct.
- 7. Enable Automatic log in.
 - Select System Settings.
 - Click Users & Groups.
 - Select the drop down menu next to the Automatically log in as setting, and select the User account.
- 8. Disable Automatic Mac Updates.
 - Select System Settings.
 - Click General.
 - Click on Software Update.
 - Click the information icon next to Automatic updates.
 - Disable Check for updates.

Measuring performance (macOS)

Cinebench 2024 benchmark

Setting up the test

 Download and install Cinebench from https://www.maxon.net/en/downloads/ cinebench-2024-downloads.

Running the benchmark

- 1. Launch Cinebench.
- 2. Select FileàAdvanced benchmark.
- 3. Set the Minimum Test Duration to Off.
- 4. Select either CPU (Multi Core), CPU (Single Core), or GPU, and click Start.
- 5. Record the result.
- 6. Wait 15 minutes before re-running.
- 7. Repeat steps 1 through 6 twice more, and report the averages of the results.

Geekbench 6 Pro

Setting up the test

Purchase a Pro license and download and install Geekbench 6 Pro from https://www.geekbench.com/download/.

Running the test

- 1. Launch Geekbench.
- 2. Click Run CPU Benchmark.
- Record the result.
- 4. Wait 5 minutes before re-running.
- 5. Repeat steps 1 through 4 twice more, and report the averages of the results.
- 6. After the first-time setup has successfully finished, the system is ready to run the benchmark.

3DMark

Setting up the test

1. Download 3DMark from the App Store.

Running the test

- 1. Launch 3Dmark.
- 2. Scroll through the benchmarks until you reach Wild Life Extreme Benchmark, and click Run.
- 3. When the benchmark run completes, record the results.
- 4. Perform steps 2 and 3 twice more, and report the averages of the results.

Speedometer 2.1

Running the test

- 1. In a browser, navigate to https://browserbench.org/Speedometer2.1/.
- Click Start Test.
- 3. When the benchmark run completes, record the results.
- 1. Perform steps 2 and 3 twice more, and report the averages of the results.

Measuring battery life (macOS)

PT custom test: Local video playback battery rundown

Setting up the test

- 1. Turn on the systems.
- 2. Copy the test video file and battery life logger to each system.
- 3. Open Terminal, and navigate to the directory containing the script.
- 4. Run chmod +x .\<script_name>.sh to make the script executable.
- 5. Set the system volume to 60 dbA with a decibel meter.
- 6. Verify that the displays will remain on during the test:
 - Select System Settings.
 - Select Lock Screen.
 - Change the following options to Never:
 - Start Screen Saver when inactive.
 - Turn display off on battery when inactive.
 - Turn display off on power adapter when inactive.
 - Require password after screen saver begins or display is turned off.
 - Return to System Settings and select Battery.
 - Set On power adapter setting to High Power (Note: this is not an option available on all Macs).
 - Click Options.
 - Disable the Slightly dim the display on battery option.
 - Return to System Settings and select Display.
 - Disable Automatically adjust brightness.
- 7. To bring up a white screen, open a web browser and type about:blank into the address bar.
- 8. Unplug the system.
- 9. Using a nit meter, adjust the screen brightness to as close to 150 nits as possible.
- 10. Plug in the system.

Running the test

- 1. Verify that the system's battery is fully charged.
- 2. Launch the test video file in full screen mode with Loop enabled.
- 3. Open Terminal and navigate to the directory containing the battery life logger script.
- 4. Type .\<battery script name>.sh and press Enter to run the script.

- 5. Unplug the system when prompted, and switch back to the full screen video.
- 6. When the system has shut down, plug in the system, and start it.
- 7. In Finder, navigate to /var/pt_results/batterylife.
- 8. Open the folder corresponding with the date and time of the test and records the results from batresults_minutes.txt.
- 9. Repeat steps 1 through 8 twice more, and report the averages of the results

PT custom test: Web browsing battery rundown

Setting up the test

- 1. Turn on the systems.
- 2. Copy the web iterator script and battery life logger to each system.
- 3. Open Terminal, and navigate to the directory containing the scripts.
- 4. Run chmod +x .\<script name> for each script to make the scripts executable.
- 5. Set the system volume to 60 dbA with a decibel meter.
- 6. Verify that the displays will remain on during the test:
 - Select System Settings.
 - Select Lock Screen.
 - Change the following options to Never:
 - Start Screen Saver when inactive.
 - Turn display off on battery when inactive.
 - Turn display off on power adapter when inactive.
 - Require password after screen saver begins or display is turned off.
 - Return to System Settings and select Battery.
 - Set On power adapter setting to High Power (Note: this is not an option available on all Macs).

- Click Options.
- Disable the Slightly dim the display on battery option.
- Return to System Settings and select Display.
- Disable Automatically adjust brightness.
- 7. To bring up a white screen, open a web browser and type about:blank into the address bar.
- Unplug the system.
- 9. Using a nit meter, adjust the screen brightness to as close to 150 nits as possible.
- 10. Plug in the system.

Running the test

- 1. Verify that the system's battery is fully charged.
- 2. Open Terminal and navigate to the directory containing the battery life logger script.
- 3. Type .\<battery script name>.sh.
- 4. Open a second Terminal, and navigate to the directory containing the website iterator scripts.
- 5. Type .\<website script name>.sh -t.
- 6. Press Enter in each Terminal window to run both scripts.
- 7. Unplug the system when prompted.
- 8. When the system has shut down, plug in the system, and start it.
- 9. In Finder, navigate to /var/pt_results/batterylife.
- 10. Open the folder corresponding with the date and time of the test and records the results from batresults_minutes.txt.
- 11. Repeat steps 1 through 10 twice more, and report the averages of the results.

This project was commissioned by Microsoft.



Facts matter.

Principled Technologies is a registered trademark of Principled Technologies, Inc. All other product names are the trademarks of their respective owners.

DISCLAIMER OF WARRANTIES; LIMITATION OF LIABILITY:

Principled Technologies, Inc. has made reasonable efforts to ensure the accuracy and validity of its testing, however, Principled Technologies, Inc. specifically disclaims any warranty, expressed or implied, relating to the test results and analysis, their accuracy, completeness or quality, including any implied warranty of fitness for any particular purpose. All persons or entities relying on the results of any testing do so at their own risk, and agree that Principled Technologies, Inc., its employees and its subcontractors shall have no liability whatsoever from any claim of loss or damage on account of any alleged error or defect in any testing procedure or result.

In no event shall Principled Technologies, Inc. be liable for indirect, special, incidental, or consequential damages in connection with its testing, even if advised of the possibility of such damages. In no event shall Principled Technologies, Inc.'s liability, including for direct damages, exceed the amounts paid in connection with Principled Technologies, Inc.'s testing. Customer's sole and exclusive remedies are as set forth herein.